



Anschlussart	DN	AD Rohr	PN	D	i	L	øB	SW	H	R	Gew.	Baureihen-Bezeichnung
	mm	mm	bar	mm	mm	mm	mm	mm	mm	mm	kg	
2  Für Rohrverschraubung leichte Reihe, DIN 2353	6	8	63	M 14 x 1,5	10	76	29	22	45	100	0,30	EMG V 063.206
	10	12	63	M 18 x 1,5	11	80	29	22	45	100	0,30	EMG V 063.210
	15	18	63	M 26 x 1,5	12	105	35	27	55	100	0,30	EMG V 063.215
7  Rohringengewinde DIN ISO 228/1	6	-	63	G 1/4	10	50	29	20	45	100	0,20	EMG V 063.706
	10	-	63	G 3/8	13	60	29	22	45	100	0,25	EMG V 063.710
	15	-	63	G 1/2	16	75	35	27	55	100	0,35	EMG V 063.715
	20	-	63	G 3/4	20	80	42	32	60	135	0,50	EMG V 063.720
	25	-	63	G 1	21	90	49	41	65	135	0,75	EMG V 063.725
	32	-	40	G 1 1/4	22	110	65	50	80	155	1,50	EMG V 040.732
	40	-	40	G 1 1/2	24	120	75	55	85	155	1,90	EMG V 040.740
	50	-	40	G 2	26	140	92	70	95	155	3,20	EMG V 040.750

Werkstoffe	PN	DN	Standardausführung
Gehäuse	40-63	6-50	Edelstahl 1.4581
Kugel	40-63	6-50	Edelstahl 1.4571
Dichtungen	40-63	6-50	PTFE

Bitte Baureihen-Bez. angeben:
EMG V 063.XXX



- Der Schaltgriff gehört zum Lieferumfang.
- Sonderausführungen auf Anfrage.