



	PN	DN	Type 1	Type 2
Body	10-40	50-100	Steel	Steel
Ball	10-40	50-100	Spheroidal cast iron, hard chromed	Spheroidal cast iron, hard chromed
Seals	10-40	50-100	NBR	PTFE

Please quote order-no. and type:
DUF (T/L) XXX.XXX / Type (1 o. 2)



- The handle is included.
- Ball valves with PTFE seals are normally delivered with FPM O-rings.
- Special designs upon request.

Flange dimensions DIN 2501 page 1	DN	PN	L	L1	D	g	K	b	z	d	H	R	SW 1	Mass	Order-No.	
	mm	bar	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	Scheme T	Scheme L
PN 10-16 Flanged ends raised face*	50	16	230	115	165	102	125	20	4	18	145	500	22	35,0	DUF	DUF
	65	16	290	145	185	122	145	22	4	18	155	500	22	47,0	T 016.065	L 016.065
	80	16	310	155	200	138	160	20	8	18	185	600	32	63,0	T 016.080	L 016.080
	100	16	350	175	220	158	180	20	8	18	195	600	32	84,0	T 016.100	L 016.100
PN 25 Flanged ends raised face*	50	25	230	115	165	102	125	20	4	18	145	500	22	35,0	DUF	DUF
	65	25	290	145	185	122	145	22	8	18	155	500	22	47,0	T 025.050	L 025.050
PN 40 Flanged ends raised face*	50	40	230	115	165	102	125	20	4	18	145	500	22	35,0	DUF	DUF
															T 040.050	L 040.050

* Further types of flange gasket facings on demand